

CONCRETE COLLAR FOR SEWER CONNECTION

GENERAL NOTES: 1. THE CURB AND GUTTER CONFIGURATION SHALL BE MOUNTABLE TYPE M CURBS AS SHOWN ON PLANS. 2. SEE STD. 606001 & AND 606301 FOR ADDITIONAL DETAILS. 3. ALL MATERIALS, LABOR, AND EQUIPMENT REQUIRED TO COMPLETE THE WORK SHALL BE INCLUDED IN THE COST OF COMBINATION CONCRETE EDGE OF CURB AND GUTTER PER LINEAR GUTTER -- BACK OF CURB FACE OF CURB -RAMPED NOSE SLOPE VARIES (TYP.) TRAFFIC

SECTION LASALLE. 95 75 STA. TO STA. FED. ROAD DIST. NO. _ ILLINOIS FED. AID PROJECT • FAP ROUTE 653 (ROUTE 18 COUPLE) ** SECTION (7)R, RS-2; (8)R, RS-1 CUTTER EDGE BACK OF CURB & GUTTER NOTE: OPENING SIZE 1'-0" SQ. IN ISLAND PAVEMENT TRAFFIC PRIMARY OPENING ISLAND SIGN POST SPACING DETAIL NOTE: THE ENGINEER SHALL DETERMINE THE NUMBER OF OPENINGS REQUIRED.

COUNTY

606-2

550-1

CONTINUOUSLY REINFORCED -WITH 3 - #4 BARS EVENLY SPACED

REINFORCEMENT SHALL NOT BE PAID FOR SEPARATELY BUT WILL BE INCLUDED IN THE CONTRACT UNIT PRICE FOR CC&G.

REINFORCEMENT DETAIL **FOR COMBINATION CONCRETE CURB AND GUTTER** TYPE B-6.24 & TYPE M-6.24

606-7

606-1